

# TVR-1208HD-4T

**TruVision DVR 12HD, HD Hybrid, 8 channel, 50% IP, 4TB**

## Overview

The TruVision DVR 12HD (TVR 12HD) is a cost-effective HD Hybrid video recorder capable of recording up to 8 or 16 camera inputs. This HD Hybrid recorder is uniquely qualified to upgrade existing analog installations, offering a competitive and practical solution for the market of HD analog, standard analog and hybrid recorders.

## A true HD hybrid

Using the open HD-TVI technology, TVR 12HD can connect any HD-TVI camera, offering HD and Full HD resolutions over existing coax cabling.

Next to HD-TVI, TVR 12HD also connects standard analog cameras, allowing you to reuse existing analog cameras which do not yet need to be replaced/upgraded.

Finally, TVR 12HD is capable of connecting up to half of its total channels to TruVision IP cameras, making this a true HD Hybrid series.

## HD-TVI technology

HD-TVI allows you to run a Full HD analog signal over existing standard coax cabling, following the same specifications as for standard analog systems today. Additionally, TVR 12HD allows you to access the local on-screen-display menu of TruVision HD-TVI cameras through over-the-coax control. This saves time in setup and facilitates maintenance afterwards.



## Detaljer

- Up to 8/16 analog cameras
- Up to 4/8 IP cameras (+4/8 analog)
- HD-TVI technology
- Over-the-coax control for TruVision HD-TVI cameras
- Use existing coax cabling for HD-TVI cameras
- Real-time HD recording
- Full HD recording at 12 fps
- Up to 4/8 TB internal storage
- Hard drive grouping & mirroring
- Text overlay for POS/ATM
- Reverse video playback
- USB archiving
- Start-up wizard for quick and easy installation
- HDMI, VGA and BNC video outputs
- V-stream support
- Front panel controls
- Operations through OSD/browser/software
- TruVision Navigator support
- Mobile app for iOS, Android & Windows Mobile
- ezDDNS
- IP Keypad support

# TVR-1208HD-4T

TruVision DVR 12HD, HD Hybrid, 8 channel, 50% IP, 4TB

## Tekniska specifikationer

### Allmänt

Teknik	HD-TVI analog
Operativ system	Embedded Linux
Monterbar på rack	Ja
Rackstorleksstorlek	1.5 U
Avtagbar fläkt	Nej
Redundant strömförsörjning	Nej

### Video-/ljudingång

Kamerakanaler	8
Stödda videokomprimeri H.264, MPEG-4 ngsstandarder	

### Lokal översikt

HDMI-utgång	1
HDMI-version	1.4
VGA-utgång	1
BNC-utgång	1
Max. lokal utdataupplösning	Full HD 1080p

### Fjärrövervakning

Programvarukompatibilit Advisor Management Software (ATS8600), et MASTerMind, OnGuard, TruPortal

Webbläsarkompatibilitet Internet Explorer

### Lagring

Lagringskapacitet	4 TB
Maximal inspelningsupplösning	Full HD 1080p
Inspelningslägen	Alarm, Event, Manual, Time-lapse high, Time-lapse low
Hårddiskredundans	Nej
Harddiskgruppering	Nej
Hot-swappable HDDs	Nej
SAS förlängning	Nej
Vänd öppen frontpanel	Nej
Automatisk arkivering	Nej
Hot reservinspelare	Nej
Edge failover-inspelning	Nej

### Nätverk

NIC-typ	RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
DNS-stöd	DDNS, ezDDNS, Ingen IP
HTTPS-stöd	Nej

### Externa gränssnitt

USB-gränssnitt tillbaka	1
USB-gränssnitt fram	1
Seriellt gränssnitt	RS-232, RS-485
Larmingångar	4
Larmutgångar	1
Max. analoga ljudutgångar	1

### Fysisk

Färg	Svart
------	-------

### Reglerande

Undfallenhet	CE, REACH, RoHS, UL
--------------	---------------------



Carrier Fire & Security förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök [se.firesecurityproducts.com](http://se.firesecurityproducts.com) online eller kontakta din försäljningsrepresentant.

Last updated on 5 May 2023 - 9:35