

# VV700NF

## Programmable Seismic Detector, Form A Relay, NFA2P

#### Universal detector

The VV700 is the first fully digital seismic detector using a microprocessor that gives 100% digital signal analysis. That means the VV700 is completely adaptable for all types of applications, without any compromises in detection ability. As the detector is programmed on site, it can be perfectly adapted to the environment and eliminate false alarms. With this new technology the detector allow room for several different signal analysis programmes in the same hardware which previously only allowed for one. This makes the VV700 to a fully universal detector suitable for all known applications like safes, vaults, vault doors, ATM's, Night Safe Deposit Boxes, weapon stores etc.

#### **Superior Detection**

The seismic detector reacts to the characteristic vibration patterns of all breaking-and-entering tools, such as hammers, drills, diamond saws, hydraulic pressure tools and thermal tools like welding torch and thermal lance. It sense vibrations that occur with a 3 to 14 meter radius of where they are mounted, depending on the material and design of the protected object.

#### SCM700 & VVI740


The Seismic Configuration Manager 700 (SCM700) is a window based software program for the programmable seismic detector VV700. The program is very easy to install on your lap-top and will give you access to plenty of new and useful features such as background signal levels, verification of the detector settings, analysing software for on-site performance measurements etc. The VV700 is delivered unprogrammed, but by using the configuration program the installer can choose from five pre-determined detector modes. Each program is tailored to a specific application. This will help you to make the most of the installation both to avoid false alarms and to have the highest performance when it comes to signal detection.

You communicate with the VV700 detector from your laptop with the configuration cable VVI740. The configuration cable VVI740 is only a tool that the installer need during the actual configuration of the detector and can be used to all his VV700 detector installations.

#### Plug-in boards & accessories

The VV700 features a plug in connection for all transponders designed in accordance with the draft standard IEC 839-2. In this way the transponder is integrated in the housing of the detector and is easily installed without any cabling or separate housing for the transponder. If you don't have your own transponder the VV700 must have another plug-in board connected to the detector e.g. the Form A relay board VVI760 or the Form C relay board VVI770.

A complete range of accessories is provided for all kinds of applications to achieve the highest security.





### Detaljer

- Universal seismic detector
- Digital signal processing
- Special configuration program SCM700
- Programmable on site equal 100% flexibility
- Easy programming from laptop
- Special analysing software for on-site performance measurements
- Compatible to all existing VV600 Plus accessories



## Programmable Seismic Detector, Form A Relay, NFA2P

## Tekniska specifikationer

Allmänt	
Ansökningstyp	Universell
Sabotage skydd	Drill shield, opening/pry-off contact
Lågspänningsalarm	7.5 V
Detektering	
Räckvidd	3 to 14 m radius
Følsomhetsjustering	5 steps of approx. 6 dB each
Elektrisk	
Strömförsörjningsvärde	9 to 13 VDC
Nuvarande förbrukning	7 mA Standby: 14 mA, Active : 64 mA (Incl. relay board VVI760/VV1770) (ROM) Standby: 7 mA, Active : 57 mA (Excl. plug-in board) (ROM)
Fysisk	
Fysiska dimensioner	80 x 100 x 33 mm (W x H x D)
Nettovikt	395 g
Färg	Grå (RAL 7035)
Miljö	
Driftstemperatur	-20 to +55°C
IP-betyg	IP30
General	
Tamper protection	Selectable, voltage 7.5 V and/or temperature +84 °C
Low/high voltage	Variable (default 7.5 V)
Low/high temperature	Variable (default -15°C / +83°C)
Inputs / outputs	
Input	Depending on plug-in board
Output	Depending on plug-in board



Carrier Fire & Security förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.